



Ed. 2023-1

DUROPLEX 900

RF AH UV



Estupenda durabilidad al exterior, retardancia de flama y aditivada con agentes antimicrobianos. Recubierta con PVDF / Outstanding outdoors durability, flame retardancy and antimicrobial agent. Coated with PVDF
CODE #21CC0000

Polyester 100%
Composición textil/Base Fabric: 1000x 1000D, 19x19
Peso/Weight > 900 ± 34 g/m² 26.5 ± 1.0 oz/sqyd
Ancho/Width > 150 cm 59.06 in
Adherencia/Ply Adhesion: >6.5 kgf
Espesor/Thickness: 0.71±0.01 mm 28 ±0.05in

Resistencia térmica (70°C, 24 h): Sin cambios
Resistencia al frío (-30°C, 2 h): No roturas ni Grietas
Flammabilidad (mm/min): 100 o menos

Resistencia a la Tensión/Tensile strenght
Longitudinal/Warp > 300 kgf / 5 cm > 290 lbf/in
Transversal/Weft > 300 kgf / 5cm > 290 lbf/in
Desgarre/Tear strenght
Longitudinal/Warp > 30 kg > 29 daN
Transversal/Weft > 25 kg > 25 daN

Elongación a la Ruptura/Enlongation at breackage
Longitudinal/Warp < 40%
Transversal/Weft < 45%

Tamaño del Rollo/Roll size > 50 m 54.68 yd
Peso del Rollo/Roll weight > 64.50 kg 148.81 lb

Usos Recomendados/Recommended uses
Cortinas laterales para camión /Truck sidiers
Carpas /Tents



21CC0054
Rojo Alfa
Alfa Red



21CC0003
Blanco
White



21CC0635
Azul
Blue

Composición física/Composition



81% PVC, 19% Polliester/Polyester fabric

www.oplex.com.mx

Teléfono/Phone: 55 5561 2300 Lada nacional sin costo: 01800 200 0807

www.oplexusa.com

OPLEX USA: (662) 570 4725 / Toll Free: 1 (866) 863 3075